



## ABS-10 Pro-Blend<sub>tm</sub> Edge Blender

### Description

Pro Blend<sub>tm</sub> is a special blend of solvents and polymer additive to aid in creating a seamless overspray edge when spraying topcoat and clear from a repair area to a non repair area. Pro-Blend maximizes flow and leveling by providing a good solvent blend and excellent surface wetting for your topcoat or clearcoat . Using Pro-Blend<sub>tm</sub> ensures a transparent, durable repair in the blended area.



### Components

- ABS-10 Pro-Blend<sub>tm</sub> Edge Blender
- Any solvent based coating



### Mixing Instructions

Mix 5 parts Pro-Blend<sub>tm</sub> Edge Blender with 1 part of your topcoat paint and gently mix just prior to painting. Two component products must be activated and reduced as you normally would mix them before combining with Pro-Blend<sub>tm</sub>.

Tip: When mixing your product for spray go ahead and mix a small portion with your edge blender and set aside for later use. Empty your gun and add blend solution when ready for blending. No need to clean gun between product and blend solution.



### Application

Apply a wet coat over the edge line of your last coat of topcoat then spray lighter coats expanding out from the edge of your last spray 12-18 inches. The goal is to provide a “taper” to the film from the edge minimizing visibility. When done properly polishing will typically remove any noticeable effects.



### Clean Up

Clean up as normally recommended for your solvent based coating recommendations.

Read MSDS of all components before using. Use proper personal protective equipment at all times. For use by professionally trained painters. **KEEP OUT OF REACH OF CHILDREN.** Bayou Innovations, LLC warrants that its products are free from defects at time of shipping. All other warranties and guaranties of any kind whether expressed or implied are disclaimed.