

EYEKANDY™ KANDY CONCENTRATES

Description

EyeKandy™ Concentrates combine proprietary polymers with premium solvents, and the true dye based candy pigments to create deep rich colors for that unique color only Kandys can exhibit. EyeKandy concentrates can be combined with intercoat clear to make Kandy basecoats, urethane clear to make 2K kandy, or simply used to strengthen existing color for a deep rich look.



Components




- **EKK Series.....EyeKandy™ Kandy Koncentrate Colors**
- **Existing color, intercoat clear or 2K Urethane clear**

Suitable Substrates



Mixes made with EKK EyeKandy Kandy Koncentrate should be applied over 2K urethane primer, or basecoat after proper flash times. The final color and depth of EyeKandy finishes is dependent on the color of the base chosen and the thickness of coats applied. Coarse Metallic bases and bases of PrismFx are well suited for EyeKandy as they give a deep, bright, and often 3D effect.

Mix Ratio



When mixing kandy colors with EyeKandy concentrates add 5-10% EyeKandy Koncentrate to intercoat clear (makes Kandy Basecoat) or ready to spray urethane clear (makes 2K Kandy). Add more or less to dial in effect desired. Spray test panels to confirm effect and adjust gun.

Application



Apply 2-4 medium coats using 75% overlap at a gun distance of 8-10 inches. Guns should be equipped with 1.3-1.5 mm tips and set for 40-55 PSI for conventional guns or 8-10 PSI at the cap for HVLP. Avoid heavy or very light coats so as to ensure good orientation of the pigments. Allow to flash 10-15 minutes between coats. As a general rule the finish should be tacky but not transfer “strings” to the finger when touches between coats. After final coat application allow to flash at least 30 minutes but then apply 2K polyurethane clear for maximum protection. If not cleared immediately allow to cure over night then scuff lightly with 600-800 grit sand paper and apply 2K clear.

Read MSDS of all components before using. Use proper personal protective equipment at all times. For use by professionally trained painters. **KEEP OUT OF REACH OF CHILDREN.** Bayou Innovations, LLC warrants that its products are free from defects at time of shipping. All other warranties and guaranties of any kind whether expressed or implied are disclaimed.